

**TOUCH-FRIENDLY.
COATINGS**



Curing schedule **Velvacoat & Moiree.**

- 5 min. at 200°C (metal temperature)
- 10 min. at 180°C (metal temperature)
- 18 min. at 170°C (metal temperature)

For an optimal result, do not cure higher than 200°C

**Some exceptional details
can only be felt.**

Look & feel.
by Protech-Oxyplast

**Passion
for powder.**

OUTDOOR
RESISTANCE

RECLAIMABLE

SOFT
TOUCH

SCRATCH
RESISTANCE



Unique look & feel

Feels less cold

Aesthetic purposes

Softer to sit on

No hitches in clothes

No scratches of coat racks

Warmer to touch

Range of beautiful metallic colours available



Special touch effects.

Velvacoat™ powder coatings offer a soft & warm touch finish to coated materials. These powders are exceptionally durable and corrosion resistant, and are the ideal finish for high-quality design products such as furniture, window frames, store fixtures, patio furniture, bike frames, bottles and any product needing that special touch. They are reclaimable, safe to spray, and environmentally friendly.



Innocoat OXYPLAST THERMOCLAD
Revêtements en poudre • Powder Coatings

Oxyplast Belgium NV
Hulsdonk 35
B-9042 Gent-Mendonk
Belgium

To place an order:
Customer Service Tel: 0032 9 326.79.30
Customer Service Fax: 0032 9 326.79.31
info@oxyplast.be

www.oxyplast.be
www.protechpowder.com